



05

Mini Excavator Vormax08

01	Model	Vormax08
02	Rated power	7kw~7.5w
03	Bucket Capacity	0.025 m ³
04	Bucket width	340mm
05	Engine Model	KOOP 192F
06	Optional Engine	BRIGGS&STRATTON
07	Operating Weight	800 kg
08	Pump form	Single gear pump
09	Set working pressure	14Mpa
10	Swing speed	12 rpm
11	Travel speed	2.2Km/h
12	Gradeability	30°
13	Ground pressure	19Kpa
14	Max. digging force	7.5KN

15	Max.digging distance	2450mm
16	Max.digging depth	1200mm
17	Max.digging height	2350mm
18	Max.dumping height	1600mm
19	Min.Swing radius	1100mm
20	Max. Upgrade height of bulldozer blade	120mm
21	Max. Digging depth of bulldozer blade	200mm
22	Total width	720-780mm
23	Total height	1300mm
24	Total length	2430mm
25	Min. ground clearance	80mm
26	Track ground length	1140mm
27	Track width	150mm
28	/	/

Multiple colors to choose from

Vormax08 Mini Excavator

EPA/CE,ISO certificate Optional: Boom swing
Color can choose Red, Yellow, Blue, accept customization



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](https://wa.me/8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10B

01	Weight	1000kg
02	Digging bucket capacity	0.025cbm/120kg
03	Bucket width	380mm
04	Engine	KOOP 192F
05	Optional Engine	Briggs & Stratton
06	Bore stroke	Single cylinder, fan cool
07	Rated power	7kw/3000r/min
08	Displacement	6.8ml/r
09	Travel speed	1.5km/h
10	Overall dimension(LxWxH)	2900 x 930 x 2180 mm
11	Wheelbase	910 mm
12	Total length of track	1230mm
13	Platform ground clearance	380 mm
14	Platform ground clearance	380 mm

15	Platform back turning radius	784 mm
16	Chassis width	896 mm
17	Track width	180 mm
18	Chassis ground clearance	132 mm
19	Track height	320 mm
20	Max. Digging depth	1750 mm
21	Max. Vertical digging depth	1550 mm
22	Max. Digging height	2610 mm
23	Max. Dumping height	1850 mm
24	Max. Digging radius on ground	3050 mm
25	Min. Rotation radius	1330 mm
26	Max. Upgrade height of bulldozer blade	345 mm
27	Max. Digging depth of bulldozer blade	255 mm
28	/	/

 Multiple colors to choose from

Vormax-10B Mini Excavator

EPA/CE,ISO certificate Optional: Boom swing
Color can choose Red, Yellow, Blue, accept closed cab, telescopic chassis



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](tel:+8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10H

01	Weight	1000kg
02	Digging bucket capacity	0.025cbm/120kg
03	Bucket width	380mm
04	Engine	KOOP 192F
05	Optional Engine	Rato,Yoop,Koop,Changchai Briggs & Stratton
06	Bore stroke	Single cylinder, fan cool
07	Rated power	7kw/3000r/min
08	Displacement	6.8ml/r
09	Travel speed	1.5km/h
10	Overall dimension(LxWxH)	2900 x 930 x 2180 mm
11	Wheelbase	910 mm
12	Total length of track	1230mm
13	Platform ground clearance	380 mm
14	/	/

15	Platform back turning radius	784 mm
16	Chassis width	896 mm
17	Track width	180 mm
18	Chassis ground clearance	132 mm
19	Track height	320 mm
20	Max. Digging depth	1750 mm
21	Max. Vertical digging depth	1550 mm
22	Max. Digging height	2610 mm
23	Max. Dumping height	1850 mm
24	Max. Digging radius on ground	3050 mm
25	Min. Rotation radius	1330 mm
26	Max. Upgrade height of bulldozer blade	345 mm
27	Max. Digging depth of bulldozer blade	255 mm
28	/	/

 Multiple colors to choose from

Vormax-10H Mini Excavator

EPA/CE,ISO certificate ,Optional Boom swing
Color can choose Red, Yellow, Blue, accept closed cab,telescopic chassis



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](https://wa.me/8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10BZ

01	Weight	1000kg
02	Digging bucket capacity	0.025cbm/120kg
03	Bucket width	380mm
04	Engine	B&S Gasoline engine/Koop
05	Rated power	10.1kw/7kw
06	Bore stroke	70x55
07	Displacement	6.8ml/r
08	Travel speed	1.5km/h
09	Overall dimension(LxWxH)	2900 x 930 x 2180 mm
10	Wheelbase	910 mm
11	Total length of track	1230mm
12	Platform ground clearance	380 mm
13	/	/
14	/	/

15	Platform back turning radius	784 mm
16	Chassis width	896 mm
17	Track width	180 mm
18	Chassis ground clearance	132 mm
19	Track height	320 mm
20	Max. Digging depth	1750 mm
21	Max. Vertical digging depth	1550 mm
22	Max. Digging height	2610 mm
23	Max. Dumping height	1850 mm
24	Max. Digging radius on ground	3050 mm
25	Min. Rotation radius	1330 mm
26	Max. Upgrade height of bulldozer blade	345 mm
27	Max. Digging depth of bulldozer blade	255 mm
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-10BZ

EPA/CE,ISO certificate ,Optional Boom swing

Color can choose Red, Yellow, Blue, accept closed cab,telescopic chassis

- 1.Steel Hydraulic hose
- 2.Comfortable & adjustable seat
- 3.Dashboard
- 4.Cylinder protection
- 5.Sound insulation



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](tel:+8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10C

01	Weight	1000kg
02	Digging bucket capacity	0.025cbm/120kg
03	Bucket width	380mm
04	Engine	KOOP (192F)
05	Rated power	10.1kw/7kw
06	Bore stroke	Single cylinder, fan cool
07	Displacement	6.8ml/r
08	Travel speed	1.5km/h
09	Overall dimension(LxWxH)	2900 x 930 x 2180 mm
10	Wheelbase	910 mm
11	Total length of track	1230mm
12	Platform ground clearance	380 mm
13	Optional Engine	BRIGGS & STRATTON
14	/	/

15	Platform back turning radius	784 mm
16	Chassis width	896 mm
17	Track width	180 mm
18	Chassis ground clearance	132 mm
19	Track height	320 mm
20	Max. Digging depth	1750 mm
21	Max. Vertical digging depth	1550 mm
22	Max. Digging height	2610 mm
23	Max. Dumping height	1850 mm
24	Max. Digging radius on ground	3050 mm
25	Min. Rotation radius	1330 mm
26	Max. Upgrade height of bulldozer blade	345 mm
27	Max. Digging depth of bulldozer blade	255 mm
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-10C

High fuel efficiency, super power. Saving energy and protecting environment



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10CZ

01	Weight	1000kg
02	Digging bucket capacity	0.025cbm/120kg
03	Bucket width	380mm
04	Engine	KOOP (192F)
05	Rated power	7kw/3000r/min
06	Bore stroke	Single cylinder, fan cool
07	Displacement	6.8ml/r
08	Travel speed	1.5km/h
09	Overall dimension(LxWxH)	2900 x 930 x 2180 mm
10	Wheelbase	910 mm
11	Total length of track	1230mm
12	Platform ground clearance	380 mm
13	Optional Engine	BRIGGS & STRATTON
14	/	/

15	Platform back turning radius	784 mm
16	Chassis width	896 mm
17	Track width	180 mm
18	Chassis ground clearance	132 mm
19	/	/
20	Max. Digging depth	1750 mm
21	Max. Vertical digging depth	1550 mm
22	Max. Digging height	2610 mm
23	Max. Dumping height	1850 mm
24	Max. Digging radius on ground	3050 mm
25	Min. Rotation radius	1330 mm
26	Max. Upgrade height of bulldozer blade	345 mm
27	Max. Digging depth of bulldozer blade	255 mm
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-10CZ

EPA/CE,ISO certificate Optional: Boom swing
Color can choose Red, Yellow, Blue, accept customization



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](tel:+8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10D

01	Weight	1000kg
02	Digging bucket capacity	0.025cbm/120kg
03	Bucket width	380mm
04	Engine	KOOP (192F)
05	Rated power	7kw/3000r/min
06	Bore stroke	Single cylinder, fan cool
07	Displacement	6.8ml/r
08	Travel speed	1.5km/h
09	Overall dimension(LxWxH)	2775 x 930 x 2219 mm
10	Wheelbase	910 mm
11	Total length of track	1230mm
12	Platform ground clearance	380 mm
13	Optional Engine	BRIGGS & STRATTON10.1kw
14	/	/

15	Platform back turning radius	784 mm
16	Chassis width	896 mm
17	Track width	180 mm
18	Chassis ground clearance	132 mm
19	Track height	320 mm
20	Max. Digging depth	1750 mm
21	Max. Vertical digging depth	1375 mm
22	Max. Digging height	2610 mm
23	Max. Dumping height	1850 mm
24	Max. Digging radius on ground	2850 mm
25	Min. Rotation radius	1330 mm
26	Max. Upgrade height of bulldozer blade	345 mm
27	Max. Digging depth of bulldozer blade	255 mm
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-10D

High fuel efficiency, super power. Saving energy and protecting environment



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10E

01	Engine	Koop/Briggs&Stratton
02	Power	7KW/10.1KWg
03	Transport length	2200mm
04	Total width	930mm
05	Upper width	805mm
06	Overall height (cab roof)	2195mm
07	Standard track plate width	180mm
08	Track gauge	750mm
09	Shovel height above ground	110mm
10	Depth of excavation of bulldozer	200mm
11	Tail turning radius	795mm
12	Track ground length	890mm
13	Track length	1235mm
14	/	/

15	Maximum digging height	2605mm
16	Maximum unloading height	1750mm
17	Maximum digging depth	1745mm
18	Maximum digging distance	2915mm
19	Minimum turning radius	1405mm
20	Maximum height at minimum turning radius	2060mm
21	Bucket capacity	0.02m ³
22	Working device form	backhoe
23	Climbing capacity	30°
24	Main valve	Tengfei
25	Weight	1000kg
26	/	/
27	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-10E



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10G

01	Weight	1000kg
02	Digging bucket capacity	0.025cbm/120kg
03	Rotation speed	12RMP
04	Climbing capacity	30°
05	Engine	KOOP 192
06	Optional Engine	BRIGGS & STRATTON
07	Main Valve	Beifang
08	Rated power	7 KW
09	Overall length / transport length	4000/2380mm
10	Overall width	940mm
11	Overall height (cab roof)	2268mm
12	Total track width	930mm
13	Main pump	Parker
14	/	/

15	Standard track plate width	180mm
16	Track gauge	750mm
17	Wheelbase	884mm
18	Track ground length	962mm
19	Track length	1204mm
20	Minimum ground clearance	100mm
21	Tail swing radius	810mm
22	Max. Digging height	2455mm
23	Max. Dumping height	1650mm
24	Max. Digging depth	1855mm
25	Max. Digging radius on ground	3050mm
26	Max. digging radius	3130mm
27	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-10G

High fuel efficiency, super power Saving energy and protecting environment



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](https://wa.me/8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-10

01	Rated power	12HP
02	Bucket capacity	0.025 m ²
03	Engine model	KOOP 192
04	Optional engine	BRIGGS & STRATTON
05	Operating Weight	900 kg
06	Max. digging force	7.5KN
07	Pump form	Single gear pump
08	working pressure	14Mpa
09	Swing speed	12 rpm
10	Travel speed	2.2Km/h
11	Gradeability	30°
12	Ground pressure	19Kpa
13	Total width	880mm
14	/	/

15	Total height	1380-1980mm (Folding safety frame)
16	Total length	2600mm
17	Min. ground clearance	100mm
18	Track ground length	1140mm
19	Track width	150mm
20	Max. digging distance	2750mm
21	Max. digging depth	1450mm
22	Max digging height	2600mm
23	Max. dumping height	1760mm
24	Min Swing radius	1100mm
25	Max. ground clearance of bu	120mm
26	Max. support depth of bulldozer	200mm
27	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-10

High fuel efficiency, super power. Saving energy and protecting environment



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](tel:+8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-12G

01	Transportation length	2380mm
02	Total width	930mm
03	Upper width	940mm
04	Total height with roof top	2270mm
05	Track width	180mm
06	Track gauge	750mm
07	Bulldozer height ground clearance	110mm
08	Bulldozer digging depth	195mm
09	Tail turning radius	820mm
10	Track grounding length	890mm
11	Track length	1235mm
12	Max. excavation height	2455
13	/	/
14	/	/

15	Engine	Kubota Z482
16	Max. dumping height	1620mm
17	Max. digging depth	1850mm
18	Max. excavation distance	2920mm
19	Min. radius	1510mm
20	Min. height at minimum turning radius	1930mm
21	Work quality	1010 kg
22	Bucket capacity	0.02m ³
23	Form of working device	Backhoe
24	Gradeability	30°
25	Main valve	soar
26	/	/
27	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-12G



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-12

01	Weight	1200kg
02	Digging bucket capacity	0.025cbm/120kg
03	Bucket width	380mm
04	Engine	Kubota D722 / 482
05	Bore stroke	Three cylinders,water cool
06	Rated power	10.2kw/2500r/min
07	Main pump	G5-6
08	Displacement	6.8ml/r
09	Swing motor	China brand
10	Traveling motor	China brand USA EATON motor(optional)
11	Travel speed	1.5km/h
12	Battery	12V 60A
13	Overall dimension(LxWxH)	2775 x 930 x 2219 mm
14	Wheelbase	910 mm

15	Total length of track	1230mm
16	Platform ground clearance	380 mm
17	Platform back turning radius	784 mm
18	Chassis width	896 mm
19	Track width	180 mm
20	Chassis ground clearance	132 mm
21	Track height	320 mm
22	Max. Digging depth	1750 mm
23	Max. Vertical digging depth	1375 mm
24	Max. Digging height	2610 mm
25	Max. Dumping height	1850 mm
26	Max. Digging radius on ground	2850 mm
27	Min. Rotation radius	1330 mm
28	Max. Upgrade height of bulldozer blade	345 mm
28	Max. Digging depth of bulldozer blade	255 mm

 Multiple colors to choose from

Mini Excavator Vormax-12


Three cylinders,water cool,Kubota Engine



Air filter
(double filters inside made in Germany)



Kubota Engine



Big size diesel tank and
hydraulic oil tank 20L

Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](tel:+8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-13

01	Transport	2325 mm
02	Total width	1100 mm
03	Upper width	990 mm
04	Total height with roof top	2270 mm
05	Track width	180 mm
06	Track gauge	920 mm
07	Bulldozer height ground clearance	105 mm
08	Bulldozer digging depth	270 mm
09	Tail turning radius	795 mm
10	Track grounding length	1050 mm
11	Track length	1545 mm
12	Climbing capability	30°
13	/	/
14	/	/

15	Engine	1230 mm
16	Optional	380 mm
17	Main valve	784 mm
18	Max. digging height	896 mm
19	Max. Dumping Height	180 mm
20	Max. digging depth	132 mm
21	Max. digging distance	320 mm
22	Min. radius	1750 mm
23	Max. height at min. turning radius	1375 mm
24	Operating	2610 mm
25	Bucket capacity	1850 mm
26	Working device form	2850 mm
27	/	/
28	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-13



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-15

Project	Vormax15	Vormax15-1	Vormax15-2	Vormax15-3	Vormax15-4	Vormax15-5
01 Vehicle Weight	1500 kg	1500 kg	1500 kg	1500 kg	1500 kg	1500 kg
02 Standard bucket capacity	0.04 M3	0.04 M3	0.04 M3	0.04 M3	0.04 M3	0.04 M3
03 Engine model	LAIDONG	KOOP 192	B&S 25T2	KOOP 292/RA TO	KUBOTA D72 2	B&S 3864
04 Rated power/speed	7 KW	7 KW	10.2 KW	12 KW	12 KW	17.5 KW
05 System pressure	9 Mpa	9 Mpa	16 Mpa	16 Mpa	16 Mpa	16 Mpa
06 Rotary speed	11 RMP	11 RMP	11 RMP	11 RMP	11 RMP	11 RMP
07 Maximum climbing angle	35°	35°	35°	35°	35°	35°
08 Walking speed (high/low speed)	3.5 Km/h	3.5 Km/h	3.5 Km/h	3.5 Km/h	3.5 Km/h	3.5 Km/h
09 Fuel tank volume	18 L	18 L	18 L	18 L	18 L	18 L
10 Wheel spacing	800 mm	800 mm	800 mm	800 mm	800 mm	800 mm
11 Total tracked	1220 mm	1220 mm	1220 mm	1220 mm	1220 mm	1220 mm
12 Platform clearance	375 mm	375 mm	375 mm	375 mm	375 mm	375 mm
13 Chassis width	980 mm	980 mm	980 mm	980 mm	980 mm	980 mm
14 Track width	180 mm	180 mm	180 mm	180 mm	180 mm	180 mm
15 Maximum ground excavation radius	2900 mm	2900 mm	2900 mm	2900 mm	2900 mm	2900 mm
16 Maximum excavation depth	1850 mm	1100 mm	1100 mm	1100 mm	1100 mm	1100 mm
17 Maximum excavation height	2450 mm	2450 mm	2450 mm	2450 mm	2450 mm	2450 mm
18 Maximum unloading height	1850 mm	1850 mm	1850 mm	1850 mm	1850 mm	1850 mm
19 Maximum vertical digger depth	1750 mm	1750 mm	1750 mm	1750 mm	1750 mm	1750 mm
20 Minimum radius of rotation	1550 mm	1550 mm	1550 mm	1550 mm	1550 mm	1550 mm
21 Maximum lifting height of shovel	150 mm	150 mm	150 mm	150 mm	150 mm	150 mm
22 Maximum depth of excavation of a bulldozer	180 mm	180 mm	180 mm	180 mm	180 mm	180 mm
23 Maximum depth of excavation of a bulldozer	180 mm	180 mm	180 mm	180 mm	180 mm	180 mm
24 /	/	/	/	/	/	//

01 Operating weight	1500 kg
02 Bucket capacity	0.04 M3
03 Battery	72 V/48 V
04 Power	4 KW
05 Battery voltage	72 V/48 V
06 Battery capacity	135 Ah
07 Battery weight	100 KG/p c
08 Working time	> 15 H
09 Track length	1090
10 Platform ground clearance	380
11 Rear-end swing radius	733
12 Width of chassis	946
13 Width of track	180
14 Height of track	320
15 Over length	320
16 Machine height	1330
17 Max. digging radius	2400
18 Max. digging depth	1650
19 Max. digging height	2490
20 Max. dumping height	1750
21 Max. vertical depth	1400
22 Min. gyration radius	1190
23 Max. lifting height of dozer blade	325
24 /	/

Multiple colors to choose from

Mini Excavator Vormax-15



koop engine




Kubota engine



B&S engine



Laidong engine



Koop water cooling engine

Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-15 Pro

01	Transportation length	2300mm
02	Total width	930mm
03	Upper width	990mm
04	Overall height (cab roof)	2270mm
05	Standard track plate width	180mm
06	Track gauge	750mm
07	Shovel height above ground	110mm
08	Depth of excavation of bulldozer	200mm
09	Tail turning radius	800mm
10	Track grounding length	890mm
11	Track length	1235mm
12	/	/
13	/	/
14	/	/

15	Engine	Koop/Briggs&Stratton
16	Working quality	1500kg
17	Bucket capacity	0.025cbm
18	Working device form	backhoe
19	Climbing capacity	30°
20	Maximum digging height	2690mm
21	Maximum unloading height	1825mm
22	Maximum digging depth	1710mm
23	Maximum digging distance	2920mm
24	Minimum turning radius	1500mm
25	Max. height at minimum turning radius	2110mm
26	/	/
27	/	/
28	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-15 Pro

Double cylinder water cool engine.



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-18-2

01	Engine	Laidong385
02	Bucket Capacity	0.04 m ³
03	Bucket Width	415 mm
04	Transport length	2550 mm
05	Ground clearance	380 mm
06	Power	39 HP
07	Track Width	200 mm
08	Digging Height	2900 mm
09	Unloading height	2000 mm
10	Wheel pitch	3227 mm
11	/	/
12	/	/
13	/	/
14	/	/

15	Weight	1800 K
16	Track Length	1500 mm
17	Digging Depth	1900 mm
18	Overall Height	2150 mm
19	Chassis width	1100 mm
20	Vertical excavation depth	1800 mm
21	Ground excavation radius	2500 mm
22	Rotary radius	840 mm
23	Machine size	2250*1100*2200 mm
24	Lifting height of shovel	325 mm
25	/	/
26	/	/
27	/	/
28	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-18-2



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-18-3

01	Engine	KUBOTA D722,KOOP 292
02	Mainvalve	BEIFANG
03	Working weight(kg)	1800 kg
04	Bucket capacity	0.03 m ³
05	Power	10.2 kw/14 kw
06	Swing speed	12 RMP
07	Gradeability	30
08	Overall length	4325/1655 mm
09	Overall width	1100 mm
10	Upper width	990 mm
11	Overall height	2272 mm
12	Standard track shoe width	200 mm
13	Track Gauge	920 mm
14	/	/

15	Min.ground clearance	119 mm
16	Tail turning radius	790 mm
17	Track ground length	1050 mm
18	Track length	1545 mm
19	Max digging height	2580 mm
20	Max.unloading height	1637 mm
21	Max.digging depth	2060 mm
22	Max.digging distance	3160 mm
23	Min.turning radius	1711 mm
24	Max.height at minimum turning radius	2048 mm
25	Boom swing Angle(left)°	75
26	Boom swing Angle(right)°	45
27	/	/
28	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-18-3



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-18-5

01	Overall dimension (L*W*H)	3865mm*1050mm*2270mm
02	Axle base(Track length on ground)	1230mm
03	Track gauge	820mm
04	Min.Ground clearance	210mm
05	Swing radius at tail	1125mm
06	Maximum Travel speed	3.5km/h
07	Width of track shoe(Rubber & steel track)	230mm
08	Number of track shoe per side(Steel track only)	38 pcs
09	Number of upper roller/ bottom roller (per side)	0/4
10	Standard bucket capacity	0.06m ³
11	Swing speed	10~12 rpm
12	Max. Grade ability	35°
13	Max. Bucket digging force	14KN
14	Max. Arm digging force	10KN

15	Hydraulic system pressure	18Mpa
16	Machine weight	1800kg
17	Emission Standard	Euro 5/EPA
18	Engine Brand / Power	Kubota D1105 14.2kw Perkins 14.7kw Laidong 3TE25 18.4kw
19	Number of cylinder	3
20	Max. Digging height	3365mm
21	Max. Dumping height	2385mm
22	Max. Digging depth	2050mm
23	Max. Vertical digging depth	1725mm
24	Max. Digging radius	3860mm
25	Min .swing radius	1720mm
26	Max. Lifting height of blade	230mm
27	Max. Cutting depth of blade	275mm
28	Boom swing angle(Left)	75°
28	Boom swing angle(Right)	45°

 Multiple colors to choose from

Mini Excavator Vormax-18-5



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-20pro

01	Transportation length	2650mm
02	Total width	970-1270mm
03	Upper width	1055mm
04	Total height with roof top	2350mm
05	Track width	200mm
06	Track gauge	770-1070mm
07	Bulldozer height ground clearance	290mm
08	Bulldozer digging depth	285mm
09	Tail turning radius	980mm
10	STrack grounding length	1200mm
11	Track length	1520mm
12	Max. excavation height	2875mm
13	/	/
14	/	/

15	Engine	Kubota/Laidong
16	Max. dumping height	1930mm
17	Max. digging depth	1995mm
18	Max. excavation distance	3130mm
19	Min. radius	1670mm
20	Min.height at minimum turning radius	2285mm
21	Work quality	1470kg
22	Bucket capacity	0.02m ³
23	Form of working device	Backhoe
24	Gradeability	30°
25	Main valve	soar
26	/	/
27	/	/
28	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-20pro



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-18Y

01	Weight	1800kg
02	Bucket Capacity	0.04m ³
03	Bucket Width	450mm
04	Engine model	Kubota722
05	Engine power	10.2kw/3600rpm
06	Climbing capacity	30°
07	Digging width	980mm
08	Track length	1500mm
09	Chassis and ground height	150mm
10	Platform and ground height	450mm
11	Overall height	2400mm
12	Max. digging force of the big arm	9.5kn
13	Bucket maximum digging force	17.2kn
14	Ravel speed	3km/h
15	Max. tractive force	22kn
16	Platform rotation speed	8-10r/min

15	Tail turning radius	830mm
16	Max. depth of dozer sinking	310mm
17	Tank capacity	14L
18	Hydraulic oil capacity	18L
19	Track center distance	775mm
20	Working pressure	17mpa
21	Tilt Angle	45°
22	Motor flow	36/min
23	Overall length	3320mm
24	Overall width	980mm
25	Max. excavation height	3225mm
26	Max. excavation radius	3470mm
27	Max. digging depth	1910mm
28	Max. vertical arm digging depth	1500mm
28	Mini. turning radius	1390mm
28	Max. clearance of dozer board	220mm

 Multiple colors to choose from

Mini Excavator Vormax-18Y



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-18-1

01	Engine	KUBOTA D722,KOOP 292
02	Mainvalve	BEIFANG
03	Working weight(kg)	1800kg
04	Bucket capacity	0.03m ³
05	Power	10.2kw/14kw
06	Swing speed	12RMP
07	Gradeability	30
08	Overall length	4325/1655mm
09	Overall width	1100mm
10	Upper width	990mm
11	Overall height	2272mm
12	Standard track shoe width	200mm
13	Track Gauge	920mm
14	/	/
15	/	/
16	/	/

15	Min.ground clearance	830mm
16	Tail turning radius	310mm
17	Track ground length	14L
18	Track length	18L
19	Max digging height	775mm
20	Max.unloading height	17m p a
21	Max.digging depth	45°
22	Motor flow	36/min
23	Max.digging distance	3320mm
24	Min.turning radius	980mm
25	Max.height at minimum	3225mm
26	turning radius	3470mm
27	/	/
28	/	/
28	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-18-1

KOOP 292F 2cylinder,KUBOTA D722 3cylinder



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-20-1

01	Engine	Laidong385 3TN25
02	Vavle	BEIFANG
03	Total length/transportation length	3337/2597mm
04	Total width	1100mm
05	Upper width	1053mm
06	Total Height	2325mm
07	Track width	200mm
08	Track Gauge	920mm
09	Mini. ground clearance	119mm
10	Tailswing Radius	1013mm
11	Track ground length	1050mm
12	Track length	1545mm
13	/	/
14	/	/
15	/	/
16	/	/

15	Working	2000kg
16	Bucket capacity	0.04m ³
17	Rated power	19KW/2200RPM
18	Revolution speed	12RMP
19	Gradeability	30°
20	Max. Digging Height	2580mm
21	Max. Dumping Height	1637mm
22	Max. digging depth	2060mm
23	Max. digging distance	3130mm
24	Min. swing Radius	1575mm
25	Height when min. swing radius	2075mm
26	/	/
27	/	/
28	/	/
28	/	/
28	/	/

 Multiple colors to choose from

Mini Excavator Vormax-20-1

Hydraulic pilot operation



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-20-3

01	Overall dimension (L*W*H)	4170mm*1300mm*2280mm
02	Axle base(Track length on ground)	1230mm
03	Track gauge	1070mm
04	Min.Ground clearance	230mm
05	Swing radius at tail	1180mm
06	Maximum Travel speed	3.5 km/h
07	Width of track shoe	230mm
08	Number of track shoe per side	38 pcs
09	Number of upper roller per side	0
10	Number of bottom roller per side	4
11	Emission Standard	Euro5/ EPA
12	Engine Model	KUBOTA
13	Power/Rotation speed	14.1kw(20HP)2000rpm
14	Optional Engine	China Laidong 22.1kw,2300rpm
15	Number of cylinder	3
16	/	/

15	Standard bucket capacity	0.1m ³
16	Swing speed	12rpm
17	Max. Grade ability	30°
18	Max. Bucket digging force	15.3KN
19	Max. Arm digging force	10.5KN
20	Hydraulic system pressure	18Mpa
21	Machine weight	2000kg
22	Arm length	1000mm
23	Max. Digging height	3700mm
24	Max. Dumping height	2290mm
25	Max. Digging depth	2450mm
26	Max. Vertical digging depth	2160mm
27	Max. Digging radius	4370mm
28	Min .swing radius	2020mm
29	Max. Lifting height of blade	240mm
30	Max. Cutting depth of blade	310mm

 Multiple colors to choose from

Mini Excavator Vormax-20-3

Japan KUBOTA engine , 14.1kw . Boom swing, Tailless rotation



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-22

01	Total length/transport length	4750 mm
02	total width	990 mm/1300 mm
03	Top Width	1050 mm
04	Total height	2470 mm
05	Track width	230 mm
06	Track Gauge	780 mm/1090 mm
07	Min.ground clearance	150 mm
08	Tail turning radius	780 mm
09	Track ground length	1200 mm
10	Track length	1500 mm
11	Max. digging height (a)	3500 mm
12	Max.unloading height(b)	2560 mm
13	PMax Digging depth(c)	2370 mm
14	Max. digging distance(d)	3030 mm
15	Min.turning radius(e)	1750 mm
16	Max. height at minimum turning radius(f)	2600 mm

15	Operating weight	2172kg	
16	Bucket capacity	0.056m³	
17	Rated power	14.2KW/2200rpm	
18	Rated speed	9.5r/min	
19	Gradeability	58%	
20	Engine	Model	KUBOTA D1105 3 cylinder direct injection
21		Rated power	14.2KW/2200
22	Main valve	Model	TRM10-BX-09-JNJT-01
23		Pressure	20.5MP
24	Main valve	Model	TFA10VO28/53R
25		Displacement	28ml/r
26	Traveling Motor	Model	KTD-490
27		Traveling speed	2.2/4.3km/h
28		Traction	18KN
29	Fuel tank Capacity	21L	
30	Cooling systerm Capacity	5.05L	

 Multiple colors to choose from

Mini Excavator Vormax-22



2.2ton with closed cabin

Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](https://wa.me/8618853773089)



05

Mini Excavator Vormax-25

01	Engine	Laidong385 3TN25
02	Vavle	BEIFANG
03	Total length/transportation length	3337/2597mm
04	Total width	1100mm
05	Upper width	1053mm
06	Total Height	2325mm
07	Track width	200mm
08	Track Gauge	920mm
09	Mini. ground clearance	119mm
10	Tailswing Radius	1013mm
11	Track ground length	1050mm
12	Track length	1545mm
13	Boom swing angle(Right)	45°
14	/	/
15	/	/
16	/	/

15	Standard bucket capacity	0.06m ³
16	Swing speed	10~12 rpm
17	Max. Grade ability	35°
18	Max. Bucket digging force	14KN
19	Max. Arm digging force	10KN
20	Hydraulic system pressure	18Mpa
21	Machine weight	2500kg
22	Max. Digging height	3365mm
23	Max. Dumping height	2385mm
24	Max. Digging depth	2050mm
25	Max. Vertical digging depth	1725mm
26	Max. Digging radius	3860mm
27	Min .swing radius	1720mm
28	Max. Lifting height of blade	230mm
28	Max. Cutting depth of blade	275mm
28	Boom swing angle(Left)	75°

 Multiple colors to choose from

Mini Excavator Vormax-25

Retractable shoes, Boom swing, Tailless rotation



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-25-2

01	Emission Standard	Tier 5/ Stage V
02	Make	KUBOTA
03	Model	D1105
04	Power /Rotation speed	14.1kw(20HP)@2000rpm
05	Number of cylinder	3
06	Maximum Travel speed	3km - 5.5km/h
07	Width of track shoe	250mm
08	Number of track shoe per side	38pcs
09	Number of upper roller per side	1
10	Number of bottom roller per side	3
11	Standard Bucket capacity	0.07m ³
12	Swing speed	9.5 rpm
13	Max. Grade ability	35°
14	Maximum Bucket digging force	19.5KN
15	Maximum Arm digging force	11KN
16	Hydraulic system pressure	21.5Mpa

15	Overall dimension (L*W*H)	3850*1300/1500*2290mm
16	Chassis Recovery	1300mm
17	Chassis Extension	1500mm
18	Axle base(Track length on ground)	1300mm
19	Min.Ground clearance	230mm
20	Swing radius at tail	750mm
21	Maximum Digging height	3980mm
22	Maximum Dumping height	2610mm
23	Maximum Digging depth	2500mm
24	Maximum Vertical digging depth	2050mm
25	Maximum Digging radius	4130mm
26	Minimum swing radius	1850mm
27	Maximum Lifting height of blade	280mm
28	Maximum Cutting depth of blade	310mm
29	Boom swing angle(Left)	75°
30	Boom swing angle(Right)	55°

 Multiple colors to choose from

Mini Excavator Vormax-25-2

Retractable shoes, Boom swing, Tailless rotation



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-26-2

01	Overall weight	2416KG
02	Bucket capacity	0.075m ³
03	Engine Model	Changchai390
04	Engine power	20KW/2200rpm
05	Overall length	3074mm
06	Overall width	1500mm
07	Overall height	2313mm
08	Hydraulic system pressure	18Mpa
09	Number of single side supporting wheel	3 pieces
10	/	/
11	/	/
12	/	/
13	/	/
14	/	/
15	/	/
16	/	/

15	Ground to upper disc distance	534 mm
16	Front and rear wheelbase	1560 mm
17	Left and right track distance	1200 mm
18	Dynamic arm deflection	45° (left)
19	Admiral's arm deflection	55° (right)
20	Tail swing radius	936 mm
21	Minimum ground clearance	230 mm
22	Maximum bucket digging force	19,5KN
23	Number of sprockets on one side	1 piece
24	/	/
25	/	/
26	/	/
27	/	/
28	/	/
29	/	/
30	/	/



Multiple colors to choose from

Mini Excavator Vormax-26-2



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](https://wa.me/8618853773089)



05

Mini Excavator Vormax-30

01	Overall length	4170mm
02	Overall width	1300mm
03	Overall height	2280mm
04	Track ground length	1230mm
05	Track gauge	1070mm
06	Min.Ground clearance	230mm
07	Swing radius at tail	1180mm
08	Max. Travel speed	3.5km/h
09	Width of track shoe	230mm
10	Number of track shoe per side	38pcs
11	Number of bottom roller per side	4
12	Emission Standard	Euro5/ EPA
13	Engine Model	KUBOTA
14	Max. Digging radius	4370mm
15	Min .swing radius	2020mm
16	Boom swing angle(Left)	75°

15	Power/Rotation speed	14.2kw(20HP)2000rpm
16	Bucket capacity	0.1m ³
17	Swing speed	12rpm
18	Max. Grade ability	30°
19	Max. Bucket digging force	15.3kn
20	Max. Arm digging force	10.5kn
21	Hydraulic system pressure	18mpa
22	Machine weight	3000kg
23	Arm length	1000mm
24	Max. Digging height	3700mm
25	Max. Dumping height	2290mm
26	Max. Digging depth	2450mm
27	Max. Vertical digging depth	2160mm
28	Max. Lifting height of blade	240mm
29	Max. Cutting depth of blade	310mm
30	Boom swing angle(Right)	45°

 Multiple colors to choose from

Mini Excavator Vormax-30



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-35

01	Transport length	5029 mm
02	Total width	1720 mm
03	Upper width	1554 mm
04	Total height	2580 mm
05	Standard track shoe width	300 mm
06	Min. ground clearance	319 mm
07	Tail turning radius	885 mm
08	Track grounding length	1645 mm
09	Track length	2150 mm
10	The height of the bulldozer blade above the ground	393 mm
11	Excavation depth of bulldozer shovel	461 mm
12	Engine	kubato D1703
13	Walking motor	Variable displacement piston motor
14	Flow sharing main valve	HVSE-09-09-P270-BE212
15	Inclined disc axial piston variable	HP5V45/AV10RB2S2MGA-L 1/1-HT1
16	/	/

15	Operation weight	3989 kg
16	Bucket capacity	0.12 m ³
17	Rated power	18.5 kw/2200 rpm
18	Rotation speed	9 r/min
19	Climbing ability	58%
20	Bucket digging force	30.4 kn
21	Excavating force of boom	18.2 kn
22	Max. excavation height	4938 mm
23	Max. unloading height	3376 mm
24	Maxi. excavation depth	3106 mm
25	Max. excavation distance	5175 mm
26	Min. turning radius	2634 mm
27	Max. height at minimum turning radius	3716 mm
28	Rated power 18.5KW/2200	Oil capacity 5.1L
29	Pressure 24Mpa	System flow rate 79.2L/min
30	System flow rate 79.2L/min	Max. speed 3250r/min

 Multiple colors to choose from

Mini Excavator Vormax-35



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-40

01	Emission Standard	Euro 5, EPA4
02	Make /Model	KUBOTA /D1703
03	Power /Rotation speed	18.5kw(25HP)@2200rpm
04	Number of cylinder	3
05	Type	In-line, water cooled, 4-stroke, mechanical pump, normally aspirated
06	Max.torque	97.4N.m/1500rpm
07	Displacement	1.647L
08	Maximum Travel speed(High/Low)	4.4/2.4km/h
09	Width of steel track shoe	300mm
10	Carrier roller(Each side)	1
11	Supporting roller(Each side)	4
12	Overall dimension (L*W*H)	4915mm*1720mm*2525mm
13	Axle base(Track length on ground)	1670mm
14	Length of rubber track	2154mm
15	Track gauge	1420mm
16	Minimum Ground clearance	295mm
17	Swing radius at tail	860mm
18	Swing radius at front	2538mm
19	Height of blade	2538mm

15	Standard Bucket capacity	3989kg
16	Swing speed	0.12m ³
17	Maximum Grade ability	18.5kw/2200rpm
18	Ground pressure	9r/min
19	Maximum Bucket digging force	58%
20	Maximum Arm digging force	30.4kn
21	Hydraulic system pressure	18.2kn
22	Machine weight	4938mm
23	Boom length	3376mm
24	Arm length	3106mm
25	Fuel tank capacity	5175mm
26	Hydraulic oil tank capacity	2634mm
27	Engine oil capacity	3716mm
28	Maximum Digging height	Oil capacity 5.1L
29	Maximum Dumping height	System flow rate 79.2L/min
30	Maximum Digging depth	Max. speed 3250r/min

15	Maximum Vertical digging depth	3208mm
16	Maximum Digging distance	2957mm
17	Maximum digging distance (on ground)	5480mm
18	Minimum swing radius	5359mm
19	Max.height when min.swing radius	2530mm
20	Maximum Lifting height of blade	3655mm
21	Maximum Cutting depth of blade	365mm
22	Boom swing angle(Left/Right)	385mm
23	Boom length	55°/65°
24	/	/
25	/	/
26	/	/
27	/	/
28	/	/
29	/	/
30	/	/

Corporate Email:
 ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
 +86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-45

01	Transport length	4400 mm
02	Transport height	2200 mm
03	Chassis width	1530/1600 mm
04	Track width	300 mm
05	Total track length	2175 mm
06	Track gauge	1703 mm
07	Plom ground clearance	557 mm
08	Engine model	ZN490
09	Power	34 KW
10	Coling method	Water-cooling Diesel e ngine
11	Operating Pressure	22 mpa
12	Waliking motor	Two speed plunger
13	Rotary motor	Variable plunger
14	The main pump	32cc Plunger 32cC
15	Flow	99/min
16	/	/

15	Max. Digging height	4450 mm
16	Max.dumping height	3050 mm
17	Max. Digging depth	2545 mm
18	Maximum digging distanc	4630 mm
19	Max.Digging radius	4730 mm
20	Minimum radius of gyration	1820 mm
21	Maximum lifting height of earth shovel	359 mm
22	The maximum digging depth of dozer	268 mm
23	Min Tail swing radius	1170 mm
24	Climbing ability	35°
25	Max. digging force	55.6KN
26	Travel speed	2.4/4.6km/h
27	Rail contact pressure on the ground	34.8kpa(0.355kgf/cm ²)
28	Bucket Capacity	0.26m ³
28	Fuel reservoir	60L
28	Hydraulic tank capacity	75L

 Multiple colors to choose from

Mini Excavator Vormax-45

High fuel efficiency, super power. Saving energy and protecting environment



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-60

01	(SAE) Bucket Capacity	0.3 m ³
02	Climbing ability	35°
03	Maximum digging force	5560N
04	Travel speed	2.4-3.8KM/h
05	Unit swing speed	8-10r/min
06	Hydraulic tank capacity	32L
07	Model	Yanmar 4TNV94
08	power	37.4/2200
09	Cooling method	water-cooling
10	Operating Pressure	28 mpa
11	L/MIN	109L/min
12	pump	Plunger
13	Walking motor	Two speed plunger
14	Shape	Load Sensing System
15	/	/
16	/	/

15	Max.Digging Height	5760mm
16	Max.Dumping Height	4030mm
17	Max.Digging Depth	3820mm
18	Max.Digging radius	6150mm
19	Minimum radius of gyration	2250mm
20	Maximum lifting height of earth shovel	359mm
21	The maximum digging depth of dozer	268mm
22	Min Tail swing radius	1170mm
23	Total weight	6000KG
24	shipping length	5850
25	Total height during transportation	5850
26	Upper shelf / chassis width	1880
27	track width	400
28	Track length	2540
28	Track gauge	1880
28	Min.ground clearance	680

 Multiple colors to choose from

Mini Excavator Vormax-60



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
[+86 18853773089](https://wa.me/8618853773089)



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-75

01	Standard Bucket capacity	0.28 m ³
02	Swing speed	11 rpm
03	Maximum Grade ability	35°
04	Maximum Bucket digging force	56 KN
05	Maximum Arm digging force	38 KN
06	Hydraulic system pressure	27 Mpa
07	Machine weight	7500 kg
08	Fuel tank	120 L
09	Hydraulic oil tank	100 L
10	Maximum Digging height	7023 mm
11	Maximum Dumping height	5195 mm
12	Maximum Digging depth	3898 mm
13	Maximum Vertical digging depth	2968 mm
14	Maximum Digging radius	6182 mm
15	Maximum Digging radius	1740 mm
16	Maximum Lifting height of blade	382 mm

15	Overall dimension (L*W*H)	6054 mm * 2216 mm * 2672 mm
16	Height of cabin	2672 mm
17	Track length on ground(Axle base)	2209 mm
18	Track gauge	1745 mm
19	Minimum Ground clearance	375 mm
20	Swing radius at tail	1730 mm
21	Emission Standard	Tier 3/ Stage III
22	Make /Model	KUBOTA(V2607)
23	Power /Rotation speed	42.4 kw (58 HP) @ 2000 rpm
24	Number of cylinder	4
25	Maximum Travel speed	2.5/4.5 km/h
26	Width of track shoe	450 mm
27	Number of track shoe per side	39 pcs
28	Number of upper roller per side	1
28	Number of bottom roller per side	5
28	Maximum Cutting depth of blade	332 mm



Multiple colors to choose from

Mini Excavator Vormax-75



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



05

Mini Excavator Vormax-80

01	Operating weight	8000 kg
02	Bucket capacity	0.3 m ³
03	Transport length	6442 mm
04	Transport width	2152 mm
05	Transport height	2835 mm
06	Tail swing radius	2057 mm
07	Track width	2600 mm
08	Min. ground clearance	318mm
09	Engine power	55/2200 kw/rpm
10	Max. engine torque	269/1610 N.m/rpm
11	Hydraulic pump (wheel pump ×2)	Shimadzu-SGPIA27F2H9
12	Certified capacity	27+27 ml/r
13	Pilot pressure	3 Mpa
14	Working pressure	20 Mpa
15	Rated flow	118.8 L/min
16	/	/

15	Hydraulic tank capacity	116 L
16	fuel capacity	138 L
17	Rotating speed	10 rpm
18	Max. travelling speed	35 km/h
19	Digging force of bucket	41.4 kN
20	Max. drawbar pull	47 kN
21	Gradeability	30°
22	Bulldozer blade (W×L)	2140/310 mm
23	Movable arm length	3500 mm
24	Arm length	1800mm
25	Max. excavation distance	6563 mm
26	Max. Digging depth	4462 mm
27	Max. Digging height	6680 mm
28	Max.dumping height	4876 mm
28	Min. turning radius	2440mm
28	/	/



Multiple colors to choose from

Mini Excavator Vormax-80

Engine: XINCHAI / YANGDONG / YUCHAI / YANMAR

Optional: Rubber Crawler or Steel Track



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Mini Excavator Vormax-90

01	Standard Bucket capacity	0.4 m ³
02	Swing speed	12 rpm
03	Maximum Grade ability	35°
04	Maximum Bucket digging force	58 KN
05	Maximum Arm digging force	40 KN
06	Hydraulic system pressure	27.5 Mpa
07	Machine weight	9000 kg
08	Fuel tank	110 L
09	Hydraulic oil tank	100 L
10	Maximum Digging height	7050 mm
11	Maximum Dumping height	5188 mm
12	Maximum Digging depth	4015 mm
13	Maximum Vertical digging depth	3550 mm
14	Maximum Digging radius	6540 mm
15	Minimum swing radius	2140 mm
16	Maximum Lifting height of blade	370 mm

15	Overall dimension (L*W*H)	6410 mm * 2278 mm * 2630 mm
16	Height of cabin	2630 mm
17	Track length on ground(Axle base)	2209 mm
18	Track gauge	1750 mm
19	Minimum Ground clearance	375 mm
20	Swing radius at tail	1813 mm
21	Emission Standard	Tier 3/ Stage III
22	Make /Model	CUMMINS/QSF2.8
23	Power /Rotation speed	53 kw (72 HP) @ 2200 rpm
24	Number of cylinder	4
25	Maximum Travel speed	2.3/4 km/h
26	Width of track shoe	450 mm
27	Number of track shoe per side	39 pcs
28	Number of upper roller per side	1
29	Number of bottom roller per side	5
30	Maximum Cutting depth of blade	344 mm

 Multiple colors to choose from

Mini Excavator Vormax-90



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089



QingDao Vormax Construction Machinery Co., Ltd.

05

Large Excavator Vormax-210

01	Standard Bucket capacity	0.4 m ³
02	Swing speed	12 rpm
03	Maximum Grade ability	35°
04	Maximum Bucket digging force	58 KN
05	Maximum Arm digging force	40 KN
06	Hydraulic system pressure	27.5 Mpa
07	Machine weight	9000 kg
08	Fuel tank	110 L
09	Hydraulic oil tank	100 L
10	Maximum Digging height	7050 mm
11	Maximum Dumping height	5188 mm
12	Maximum Digging depth	4015 mm
13	Maximum Vertical digging depth	3550 mm
14	Maximum Digging radius	6540 mm
15	Minimum swing radius	2140 mm
16	Maximum Lifting height of blade	370 mm

15	Overall dimension (L*W*H)	6410 mm * 2278 mm * 2630 mm
16	Height of cabin	2630 mm
17	Track length on ground(Axle base)	2209 mm
18	Track gauge	1750 mm
19	Minimum Ground clearance	375 mm
20	Swing radius at tail	1813 mm
21	Emission Standard	Tier 3/ Stage III
22	Make /Model	CUMMINS/QSF2.8
23	Power /Rotation speed	53 kw (72 HP) @ 2200 rpm
24	Number of cylinder	4
25	Maximum Travel speed	2.3/4 km/h
26	Width of track shoe	450 mm
27	Number of track shoe per side	39 pcs
28	Number of upper roller per side	1
29	Number of bottom roller per side	5
30	Maximum Cutting depth of blade	344 mm

 Multiple colors to choose from

Mini Excavator Vormax-90



Corporate Email:
ethan@qingdaovormaxmachinery.com

WhatsApp/WeChat:
+86 18853773089